

The Flownex SOLO is a compact and versatile validator designed for seamless integration into any vehicle equipped with AVL and AFC systems. It offers a smart and secure solution for payment, location-based, and online services. Powered by a quad-core ARM Cortex-A7 CPU running up to 1.2GHz, and featuring a 2.8-inch full-color TFT LCD, the Flownex SOLO combines advanced technology with a user-friendly interface.

Its compact size and easy installation make it the ideal choice for modern transit needs, ensuring convenience and security for all users.





CPU

Display

RAM

Storage

External Storage

Operating System

Connectivity

Cellular Network

GNSS

QR Code Scanner

Card type Support

SAM

External Communication

Audio

Power

Operating Temperature

Dimensions

Mounting Type

Quad Core ARM Cortex-A7 up to @1.2GHz

2.8-inch full-color TFT LCD

512 MB

8GB eMMC

MicroSD slot supporting up to 128GB

Linux

• Wi-Fi 802.11b/g/n, Bluetooth4.0,

• Ethernet 10/100 Mbps (optional)

4G-LTE, NB-IoT (optional)

GPS / GLONASS / BeiDou

• 5 MP Camera with 1080p

• ISO 18092 (NFC), MiFare, DESFire

ISO 15693, ISO 14443A/B

2 x on board

RS232, RS485, USB (optional)

Buzzer

9–38 Vdc with Reverse Polarity and Over-Voltage Protection

-20°C to +60°C

130 X 60 mm, 130 X 100 mm with Clamp

Pole Mounting



